

# Forkster

Part # FSTR

## Features



- *Load-stabilizing wheels designed to maintain stability and prevent tipping*
- *Applies only minimal stress to the skidloader arms*
- *Adjustable arm width to handle many different lengths of materials*
- *Sturdy tread tires that turn easily on any terrain*
- *15° of tilt in both directions*
- *3 stage mast*
- *16 foot height*
- *Pressure down safety valve*
- *Optional truss boom available*

## Specifications

**Lift Height:** 15.2 Feet  
**Max Lifting Capacity:** 3,300 Lbs @ 7 Feet  
2,500 Lbs @ 12 Feet  
1,200 Lbs @ 16 Feet  
**Tires Size:** 20.5 x 8-10  
**Tire Rating:** 4-Ply Sidewall, 5-Ply Tread, 90 PSI  
**Wheel:** 10 x 7.5 with 5 x 4.5 Bolt Circle  
**Clearance Height:** 101" With Forks Lowered  
**Clearance Width:** 93" Outside tires (innermost position)  
Up to 136" Extended  
**Hydraulic Spec:** Minimum Pressure: 1,500 PSI  
Minimum flow: 6 GPM  
**Weight:** 1850 Lbs Without Forks



**HOSES INCLUDED. COUPLER KIT SOLD SEPARATELY  
SEE PG 955 FOR MORE INFORMATION**

Suggested List Price Pg 955